


SPC-4 Typical Application

The SPC-4 provides basic control of a video projector or other display where no control of sound is required.



Typical Use

Classrooms, small meeting rooms, exhibitions, hotels, bars & restaurants or anywhere where control over a display is required and sound is either not required or handled by other means.

Description

The SPC-4 is connected to the RS232 port of the display to control power and input select. It supports selection of 1 x PC input and 2 x Video input allowing both composite video and HDMI to be used. Inputs to the display can be directly connected or fed via wall panels as illustrated.

Control and installation

To program the unit it is only necessary to download a library module for complete control over the display. Full customisation over input selection (e.g. warm up and cool down times) is also provided.

Accessories

The SPC-4 is supplied complete with a white UK size mounting frame and a 12V power supply. Please select input panels from our wide range available in a variety of configurations.

The SPC-4 can be fitted into one of our desk access modules along with input panels from our Euro range.

Kit List

For the system as illustrated you will need:-

1 x SPC-4	£	108.00
1 x EP- PC25, XVGA input panel	£	19.50
1 x EP-V25, video input panel	£	14.25
1 x EP-HDMI50, HDMI input panel	£	20.00
1 x EP-100FW, white frame for input panels	£	<u>6.83</u>
UK List Total Cost	£	168.58

In addition you will need the following cables:-

Qty	Type	From	To
1	RS232	SPC-4	Display
1	VGA	PC input panel	Display
1	Video Coax	Video input panel	Display
1	HDMI	HDMI input panel	Display